



# SOFTENER

## PLUS IRON FILTRATION

### *Hardness, Iron & Manganese*

- Softens water and removes unwanted iron and manganese
- Hybrid regeneration for efficiency and improved water quality



ANTIMICROBIAL  
TECHNOLOGY



CONTROL VALVE



PRESSURE TANK



- Softens water and removes up to 10 ppm of ferrous or ferric iron
- Metered regeneration for efficiency and improved water quality
- Quick-connect fittings (includes straight and 90-degree elbow connectors)
- Provides high-capacity flow for reliable access to high-quality water
- Customized to your individual needs, including household size and plumbing
- System-level certified by IAPMO R&T to NSF/ANSI Standard 42, 44, 61 & 372
- Made in an IAPMO-certified manufacturing plant



# COMPONENTS & SPECIFICATIONS

## SOFTENER SYSTEM SPECIFICATIONS

### BRITA PRO® SOFT + IRON PLATINUM SERIES 1"

- \*Fully customizable programming including times and cycle order
- \*Low Battery Warning
- \*Service Technician "Step-Through" Regeneration
- \*Service Call Reminder (not programmed from factory)

- \*Stores system configuration and operation data in nonvolatile memory
- \*Programmable contractor contact screen
- \*Multiple Regenerations per day
- \*Valve internally ported in 1 inch

- \*Color specific displays
- \*Easy contractor set-up, program time of day and hardness
- \*Battery back-up with up to 8 hrs of power carry-over
- \*Treated water brine refill
- \*Days override feature: 1-28 days available

- \*External Accessory Operation
- \*Optional Air Release Cycle
- \*Water drop flow indicator
- \*Factory-set pre-fill brine
- \*Scrolling Text Display

- \*62 days diagnostic information including, flow rates, gallons since regeneration, days since regeneration, total regenerations since start up, peak flow rates, and days till regeneration

Part Number	BPFS100J	BPFS150	BPFS200
Salt Used - Per Regeneration (Lbs)	15	22	30
Regeneration Programming	Pre-Fill Brine	Pre-Fill Brine	Pre-Fill Brine
Grains Capacity	32,000	45,000	60,000
Resin Quantity (FT3)	1	1 1/2	2
Mineral Tank	10x54	12x52	13x54
Tank Jacket	YES	NO	NO
Media Loaded	YES	NO	NO
Brine Tank Size	15x36	15x36	15x36
Salt Storage Capacity	275	275	275
Service Flow Rate	13	14	16
Pipe Size (IN.)	1	1	1
Min-Max Pressure (psi)	20-100	20-100	20-100
Min-Max Temperature (°F)	35-100	35-100	35-100
Backwash GPM	1.7	1.7	1.7
Plumbing Connections	1 inch Male NPT Elbow	1 inch Male NPT Elbow	1 inch Male NPT Elbow
Bypass	YES	YES	YES
Total Height (IN.)	61	59	61

## SOFTENER SYSTEM DIMENSIONS

Part Number	BPFS100J	BPFS150	BPFS200
A measurement	61 in	59 in	61 in
B measurement	10 in	12 in	13 in
C measurement	16.5 in	18.5 in	19.5 in
D measurement	36 in	36 in	36 in
E measurement	15 in	15 in	15 in
F measurement	17 in	17 in	17 in

